



- 1. Put the car into gear or park and apply the hand brake, loosen the rear wheel nuts on one side, raise the vehicle on a trolley or bottle jack under the axle and then support the vehicle with an axle stand under the chassis. It's easier and safer to do this job one side at a time.
- 2. Remove the rear wheel.
- 3. Remove both of the bolts that secure the spring seat to the axle.
- 4. Discard the standard spring retainer if fitted.
- 5. Re-use the bolts to secure the new spring retaining plate to the spring seat and the axle case on top of the bottom most coil of the spring and then tighten them both to the manufacturers torque setting.
- 6. Refit the wheel, lower the car off of the axle stand and torque the wheel nuts correctly.
- 7. Repeat the procedure on the other side.

WARRANTY & DISCLAIMER - Terrafirma products are warranted free from defects in materials and workmanship for a period of 12 months from the date of retail invoice. Terrafirma does not warrant that the products manufactured or marketed by it comply with the laws of the country where those goods are purchased or used. It is the sole responsibility of the purchaser to ascertain whether products being purchased, or the fitting of those products to any other object, comply with local laws. This warranty covers structural defect and workmanship but does not cover finishes, labour charges for removal or refitting, freight costs, accident damage, misuse or abuse, damage due to incorrect or improper fitment or application, montified product, faulty design or consequential damage of any kind. Damage or defects cause dby collision, alteration, improper installation, road hazards, adverse conditions or usage for any other purpose other than normal private usage are not covered by this warranty. Terrafirma shall not be liable for any other claim relating to the use of the product and any indirect special or consequential damage or injury to any person, company or other entity. All claims must be accompanied by the original retail invoice and should be submitted to the supplying Allmakes 4x4/Terrafirma distributor. This warranty covers only the replacement of the product or part concerned. The decision remains solely at the discretion of Allmakes/Lerdiffrma distributor for the latest product specifications without notice. Always consult your Allmakes/Terrafirma distributors. The Terrafirma and is associated companies reserve the right to alter the range and any product specifications without notice. Always consult your Allmakes/Terrafirma distributor for the latest product information and specifications. The Terrafirma ange of products is constantly being evaluated for enhancement and improvement to make sure the level of quality and performance is as expected.